

Straight Microduct Connector



Description

- Connect two microducts which are the same outer diameter
- Easy installation, without any special tools
- Transparent plastic body, easy to observe the situation
- High temperature resistance -40°C ~65°C
- High pressure resistance >25bar
- Standard EN50411-2-8
- ※FR Resistance styles also available

Specification	Duct OD/ID(mm)	PCS/CTN
STR3/2.1	3/2.1	5000
STR4/2.5	4/2.5	3000
STR5/2.1	5/2.1	3000
STR5/3.5	5/3.5	3000
STR6/4	6/4	3000
STR7/3.5	7/3.5	2000
STR7/4	7/4	2000
STR7/5.5	7/5.5	2000
STR8/3.5	8/3.5	2000
STR8/5	8/5	2000
STR8/6	8/6	2000
STR8.5/6	8.5/6	2000
STR10/6	10/6	1000
STR10/8	10/8	1000
STR12/8	12/8	1000
STR12/9	12/9	1000
STR12/10	12/10	1000
STR12.7/10	12.7/10	1000
STR14/10	14/10	800
STR14/12	14/12	800
STR15/12	15/12	800
STR16/12	16/12	600
STR16/13	16/13	600
STR18/12	18/12	400
STR18/14	18/14	400