

Reducer Microduct Connector



Description

- Connect two microducts which are different outer-diameter
- Internal cone hole to prevent fiber hang up
- Easy installation, without any special tools
- Transparent plastic body, easy to observe the situation
- High temperature resistance -40 C ~65 C
- High pressure resistance >25bar
- Standard EN50411-2-8

Specification	Duct OD/ID(mm)	Duct OD/ID(mm)	Taper Hole(mm)	PCS/CTN
BRE5-3/2.1	5/3.5	3/2.1	3.5>2.1	3000
BRE5-4/2.8	5/3.5	4/2.8	3.5>2.8	3000
BRE7-3/2.1	7/5.5	3/2.1	5.5>2.1	2000
BRE7-4/2.8	7/5.5	4/2.8	5.5>2.8	2000
BRE7-5/3.5	7/5.5	5/3.5	5.5>3.5	2000
BRE8-3/2.1	8/6	3/2.1	6>2.1	2000
BRE8-5/3.5	8/6	5/3.5	6>3.5	2000
BRE8-7/3.5	8/6	7/5.5	6>5.5	2000
BRE10-5/3.5	10/8	5/3.5	8>3.5	1000
BRE10-7/5.5	10/8	7/5.5	8>5.5	1000
BRE10-8/6	10/8	8/6	8>6	1000
BRE12-5/3.5	12/10	5/3.5	10>3.5	1000
BRE12-7/5.5	12/10	7/5.5	8>5.5	1000
BRE12-8/6	12/10	8/6	8>6	1000
BRE12-10/8	12/10	10/8	10>8	1000
BRE12.7-12/10	12.7/10	12/10	12.7>10	1000
BRE14-7/3.5	14/10	7/3.5	10>3.5	1000
BRE14-10/8	14/12	10/8	12>8	1000
BRE14-12/10	14/12	12/10	12>10	1000
BRE16-10/8	16/13	10/8	13>8	800
BRE16-12/10	16/13	12/10	13>10	600
BRE16-14/10	16/13	14/10	13>10	600
BRE18-14/10	18/14	14/10	14>10	500