

Fiber Optics Distribution Box

GP31-1P04B

Overview

Optical distribution box terminates one fiber optic cable with up to 4 cores, bringing significant improvements resulting in better customer experience when FTTH have to be deployed.

Features

- ABS material used ensures the body strong and light.
- Easy installations: Mount on wall or just put on the ground.
- Splicing tray can be removed when needed or during the installation for the convenient operation and installation;
- Adapter slots adopted – No screws needed for installing adapters.
- Double-layer design for easier installation and maintenances:
 - ✧ Upper layer for splicing.
 - ✧ Lower layer for distribution.
- Cable fixing units provided for fixing the outdoor optical cable.
- Accommodates both cable glands as well as tie-wraps
- Fully stable patch panel, no risk of movement.
- Protected patch panel offers secure environment for adapters, patch cords and pigtails.



Dimensions and Capability

Adapter Capacity	4 fibers with SC / FC / LC adapters
Number of Cable Entrance/Exit	1/4
Optional Accessories	Adapters, Pigtails
Weight	0.16 KG
Max diameter of entry cable	13mm

Operation Conditions

Temperature	-5°C -- 60°C
Humidity	90% at 30°C
Air Pressure	70kPa – 106kPa

Shipping Information

Package Contents	Distribution box, 1 unit; Wall mount installation accessories, 1 set
Material	Carton box
Weight	0.65 KG
Lead Time	10-15 working days normally