


# Fiber Optics Distribution Box

## Overview

This distribution box terminates up to 2 fiber optic cables, offers spaces for splitters and up to 48 fusions, allocates 24 SC adapters and working under both indoor and outdoor environments. It is a perfect cost-effective solution-provider in the FTTx networks.



## Features

- ABS with PC material used ensures the body strong and light.
- Water-proof design for outdoor uses.
- Easy installations: Ready for wall mount – installation kits provided.
- Adapter slots used – No screws and tools needed for installing adapters.
- Ready for splitters: designed space for adding splitters.
- Space saving: double-layer design for easier installation and maintenance:  
Upper layer for splitters and distribution or for 24 SC adapters and distribution.  
Lower layer for splicing.
- Cable fixing units provided for fixing the outdoor optical cable.
- Protection Level: IP55.
- Accommodates both cable glands as well as tie-wraps.
- Lock provided for extra security.
- Max allowance for entry cables: max diameter 15mm, up to 2 cables.
- Max allowance for exit cables: up to 24 simplex cables.



## Dimensions and Capability

Weight	1.8KG
Adapter Capacity	24 pcs
Number of Cable Entrance/Exit	Max diameter 15mm, up to 2 cables
Optional Accessories	Splitters, adapters, pigtails, splice trays, heat shrink tubes

## Operation Conditions

Temperature	-40°C -- 60°C
Humidity	93% at 40°C
Air Pressure	62kPa – 101kPa

## Shipping Information

Package Contents	Terminal box, 1 unit; Keys for lock, 2 keys; Wall mount accessories: 1 set
Material	Carton Box
Weight	3.5KG
Lead Time	10-15 working days normally