

Fiber Optics Distribution Box

Overview

This mini style distribution box is widely applied in the FTTX network to connect drop cable and ONU devices through fiber port. It supports splicing, distribution, mechanical connection and wall mounted installation. GP31-1P08A fttth optical distribution box can be installed with 8 pcs sc fiber optic adapter to fix and splice & fiber optic pigtails. This 8 cores fttth optical distribution box applies to the inlet of indoor fttth drop cable, the maximum length of fiber storage is 15m

Features

- ABS material used ensures the body strong and light
- Reasonable inner design for optical fiber
- Small size, light weight, good appearance
- Capacity of 8 cores basically
- Suitable for SC fiber adapter
- Easy for fiber bending radius and operation
- Wall-mount with mechanical protection

Dimensions and Capability

Adapter Capacity	SC Duplex 8 Cores
Number of Cable Entrance	Max Diameter 18mm*Q2
Weight	0.46 KG
Optional Accessories	Adapters, Pigtails, Heat Shrink Tubes
Installation	Wall-Mounted

Operation Conditions

Temperature	-5°C -- 60°C
Humidity	90% at 30°C
Air Pressure	70kPa – 106kPa

Shipping Information

Package Contents	Mini terminal box, 1 unit; Wall mount installation accessories, 1 set
Material	Carton box
Weight	0.85kg
Lead Time	10-15 working days normally