

STRUCTURE CABLING

PATCH CORD

U/UTP unshielded twisted 4 pairs category 6 flat patch cord



Standard

- Electrical performance guaranteed to meet or exceed ANSI/TIA-568B Category 6 and ISO/EIC specifications.
- Independently tested and verified intertek(ETL).
- Ideal for Data center architectural requirements.
- Stranded cable for maximum flexibility.
- Available with different plug mold.
- Available with different color of cable.
- Available with different length.

Conductor

Conductor	stranded bard copper 32AWG
Insulation	HDPE
Total number of insulated conductors	8, twisted in 4 pairs
Color code	blue x white, orange x white, green x white, brown x white
Individual pair shield	None
Overall shield	None
Drain wire	None

Nominal Transmission Characteristics

Res.	Length	Prop. Delay	Delay Skew	Freq.	Insertion Loss	NEXT	RL	ACR-N	ACR-F	PS NEXT	PS ACR-N	PS ACR-F
Ω	Max.	ns	ns	MHz	dB	dB	dB	dB	dB	dB	dB	dB
i	20m	555	50	1	3	65.0	19.0	62.0	63.3	62.0	59.0	60.3
				4	4	63.0	19.0	59.0	51.2	60.5	56.5	48.2
				8	5.7	58.2	19.0	52.5	45.2	55.6	49.9	42.2
				10	6.3	56.6	19.0	50.2	43.3	54.0	47.7	40.3
				16	8	53.2	18.0	45.2	39.2	50.6	42.6	36.2
				20	9	51.6	17.5	42.6	37.2	49.0	39.9	34.2
				25	10.1	50.0	17.0	39.9	35.3	47.3	37.2	32.3
				31.25	11.4	48.4	16.5	37.0	33.4	45.7	34.3	30.4
				62.5	16.5	43.4	14.0	26.9	27.3	40.6	24.1	24.3
				100	21.3	39.9	12.0	18.6	23.3	37.1	15.8	20.3
				200	31.5	34.8	9.0	3.3	17.2	31.9	0.3	14.2
				250	35.9	33.1	8.0	-2.8	15.3	30.2	-5.8	12.3