

Keystone Jack



VK-80285-C7



VK-80285-C8



VK-81245-C6A



VK-81255-C6A



VK-81265-C6A



VK-81275-C6A



VK-59195-C8



VK-80385-C8



VK-99165-C8



VK-99175-C8



VK-99185-C8



VK-99195-C8

Description

- FTP Type: 1 Piece Design
- Easy Assembly: Easily terminated in the field in 2 minutes without any special tools
- Wire Connection: Standard wire AWG 27/7 to 22/7
- Wire Connection: Solid wire AWG 26/1 to 22/1
- It suitable according to IEEE 802.3an
- Suitable for power over ethernet(PoE, PoE plus, and UPoE)
- Cable Jacket Diameter from 6 to 9.5mm
- Adjust Stain Relief (6mm to 9.5mm Cable OD)
- Load bar for fast and easier wire pattern termination
- Reconnectable

Parameter

- Operation Temperature: -40°C-60°C.
- Relative Humidity: 85%(30°C)
- Air Pressure: 70-106Kpa
- Gold Plated Phosphor Bronze Blade: Phosphor bronze and gold plating, (30-50uinch), mating durability not less than 750 cycles;
- Anti-burn Performance: Product made from Kirsite / PC or PCB(UL94V-0), meeting the international standard;
- Intermediate Resistance: No more than 20m ohm in normal atmosphere pressure;
- Intensity of anti-current: DC 1,000V(AC, 700V), no puncture and flash -over phenomenon in one minute;
- Retention strength: 7.7kg between jack and plug;
- Label: Clear label to ensure easy to management.