

OUTDOOR CABINETS

HS-0D05

Standard

- Comply with ANSI/EIA,RS-310-D;IEC297-2; DIN41491:PART1;DIN41494:PART7;GB/T3047.2-92 standard and ETSI standard.
- Certification: CE,RoHS,SGS,ISO,REACH

Material and Size

- Materials: SPCC cold rolled steel or EG steel
- Thickness: Mounting profile:1.5 mm, others:1.00 mm to 1.20 mm
- Width: 600 mm
- Depth: 450/600 mm
- Height: 4U, 6U, 9U, 12U, 15U, 18U, 22U, 27U
- Structure: 19" installation

Colour

- Color: RAL9005(Black);RAL7035(Grey)

Loading Capacity

- Max loading capacity: 60KG



OUTDOOR CABINETS

HS-OD05

Details



Common lock



Hinge view



Grey color rail
(Silver silk printed U)



Earthing cable at door



Cable entrance with
waterproof flange



AC cooling fan (IP55 only)

Feature

- Material: SPCC cold rolled steel
- Thickness: 0.8mm, 1.0mm, 1.2mm, 1.5mm, 2.0mm and etc are all available to be designed for the material used
- Processing: Laser cutting, CNC punching, CNC bending, Hand welding, stamping, etc
- Surface treatment: Painting, Plasma electrostatic painting, hot galvanized, powder coating, polishing, brushing, cataphoresis, etc
- Certification: ISO9001:2000 , CE, RoHS , SGS
- IP degree: IP55&65
- Water proof: 0.2Mpa,10mm/min,30min,Endure water pressure 0.2Mpa; Water spray intensity :10mm/min .(for 30 min)
No leakage inside Comply with GB 4208-1993 IP65 standard
- Fire proof: Non-metal marterial burning time< 1s(put onto blue fire over 30s)
- Noise proof: < 55db
- Voltage test: Comply with 48V DC or 220V AC
- Resistance test: Resistance test
- Working environment: Can normally work from -30°C to 65 °C
- Tolerance: +/-3mm

Dimensions list

Model No.	Width×Depth×Height
HS-OD05-6606	600×600×6U mm
HS-OD05-6609	600×600×9U mm
HS-OD05-6612	600×600×12U mm
HS-OD05-6615	600×600×15U mm
HS-OD05-6618	600×600×18U mm

